



PRODUCT DESCRIPTION

Next CABLELOC™ conduit is specifically designed for the installation of wires and cables, supporting a continuous operating temperature of 75 °C, in compliance with the Canadian Electrical Code, Part I, for ordinary locations. Its smooth interior surface facilitates cable pulling and prevents costly cable damage. CABLELOC™ is highly UV-resistant and offers excellent tensile and impact strengths, even in cold weather conditions.

FUNCTION

Protects cables with a smooth interior surface that facilitates pulling and minimizes potential damage. Suitable for exposed, concrete encased, and direct burial applications.

RAW MATERIALS

High-impact, UV-resistant polyvinyl chloride (PVC) compound, engineered to meet CSA standards for electrical conduit applications

AVAILABLE ACCESSORIES

Elbows, couplings, adapters, end caps, etc

COMPLIANCE STANDARDS

Certified to:

- **CSA C22 No. 211.2**

Conforms to:

- **UL 651**
- **NEMA TC 2**

FEATURES

- Allows for easy wire pulling
- UV resistant
- High tensile and impact strength, even in cold weather
- Solvent cementing is the only process needed, removing the necessity for power-threading machines, pipe vices, or cutting tools.



561-842-2743
863-357-3300

✉ info@nextinfrass.com

🌐 nextinfrass.com

CABLELOC DIMENSIONS

Nominal Size		ID		Min. Wall		OD	
inches	mm	inches	mm	inches	mm	inches	mm
1/2	12	0.622	15.8	0.109	2.77	0.840	21.3
3/4	20	0.824	20.9	0.113	2.87	1.050	26.7
1	25	1.049	26.6	0.133	3.38	1.315	33.4
1-1/4	32	1.380	35.0	0.140	3.56	1.660	42.2
1-1/2	40	1.610	40.9	0.145	3.68	1.900	48.3
2	50	2.067	52.5	0.154	3.91	2.375	60.3
2-1/2	65	2.469	62.7	0.203	5.16	2.875	73.0
3	75	3.068	77.9	0.216	5.49	3.500	88.9
3-1/2	90	3.548	90.1	0.226	5.74	4.000	101.6
4	100	4.026	102.3	0.237	6.02	4.500	114.3
5	125	5.047	128.2	0.258	6.55	5.563	141.3
6	150	6.065	154.1	0.280	7.11	6.625	168.3
8	200	7.978	202.6	0.322	8.18	8.622	219.0

CABLELOC BUNDLE SIZES & WEIGHTS

Nominal Size		Product code	Length (ft)*	Bundle Type A	
inches	mm			Pcs. / Length in ft	Weight (lbs)
1/2	12	117001-118	10	600 / 6000	910
3/4	20	117011-118	10	440 / 4400	890
1	25	117021-118	10	360 / 3600	1080
1-1/4	32	117031-118	10	330 / 3300	1360
1-1/2	40	117041-118	10	225 / 2250	1105
1-1/2	40	117041-114	20	225 / 4500	2210
2	50	117051-118	10	140 / 1400	1045
2	50	117051-114	20	140 / 2800	2090
2-1/2	65	117061-118	10	78 / 780	925
3	75	117071-118	10	78 / 780	1210
3-1/2	90	117072-118	10	63 / 630	1175
4	100	117081-118	10	60 / 600	1325
5	125	117091-188	10	23 / 230	690
6	150	117101-118	10	26 / 260	1010
6	150	117101-114	20	26 / 520	2020
8	200	117111-118	10	14 / 140	820

Note: The values listed in the tables are approximate and may change without notice